

IVORY SERIES



*Weathering with
the bright*

- Outdoor fixed installation
- High-end solution for DOOH cases

Application

- Billboard & Banner
- Outdoor signage DOOH



WATERPROOF



LOW POWER



ROBUSTNESS



EASY
MAINTENANCE

Specification List


Product Name	Ivory-4	Ivory-5	Ivory-6	Ivory-8	Ivory-10	Ivory-16
Pixel Pitch (mm)	4.166	5	6.25	8.33	10	16.67
LED Type	SMD					
Pixel Density (dot/m ²)	57600	40000	25600	14400	10000	3600
Module Size(mm)	400*200					
Panel Size(mm)	800*800*91.55					
Panel Resolution(dot)	192*192	160*160	128*128	96*96	80*80	48*48
Panel Material	Aluminum/Iron					
Panel Weight(kg/pcs)	25/35	22/30	22/30	22/30	22/30	22/30
Brightness(cd/ m ²)	5500	5500	6500	6500	6500	6500
Hori.& Vert. Viewing Angel(Deg)	140/110					
Contrast Ratio	4000:1	4000:1	4000:1	4000:1	4000:1	4000:1
Max.& Avg.Power Cons.(W/ m ²)	810/280	810/280	810/280	960/336	960/336	960/336
Refresh Rate (Hz)1920	1920					
Maintenance Way	Front or Rear					
Installation Way	Front or Rear					
IP Rate	IP67/IP65					

Note: * Specifications are slightly different according to different configurations.
* All rights reserved to SHISAI.



Non-cabinet version

- Direct module mounting so that less installation structure & cost is achievable



Air valve

- Avoid the distortion of module caused by air pressure



Added thermal management

- Additional aluminum board for the heat dissipation of dense pixels (P4.1)


Super water-proof

- Enclosed-designed module which could reach IP67



Fully front or back maintenance

- Quick module lock & tip power box readily achieve convenient maintenance & perfectly suit for all kinds of environment



Isosceles trapezoid module design

- 90° Corner & curved display are available

